



Ceramic roof tiles
and accessories

ROOF TILES





Technical data*


Weight (1 item)	ca. 3.90 kg
Total length	ca. 46.6 cm
Total width	ca. 30.6 cm
Length of cover	ca. 35.7–39.8 cm
Average width of cover	ca. 24.3 cm
Minimum design value/m ²	ca. 10.3 items
Quantity/m ²	ca. 10.3–11.5 items
Minimum roof inclination angle	up to 22°
Quantity/EURO pallet	240 items
Weight per sqm	ca. 40.2–44.9 kg
Weight of full pallet	ca. 966 kg
Frost resistance	yes

* technical parameters may be slightly changed

Properties

- aesthetic and solid appearance
- larger format
- allows the use of different fixing brackets
- displacement tolerance of up to 41 mm
- deeper and higher locks

Elegant, traditional
effect of wavy
lines



Roof battens 30×50 mm


MILANO	LAF/FLA (mm)											
Roof inclination angle	10°	14°	18°	22°	25°	30°	35°	40°	45°	50°	55°	60°
GAŚIOR												
LAF	58	58	56	56	56	56	54	54	54	54	54	54
FLA	164	158	152	146	142	136	130	124	116	110	104	98

Roof battens 40×60 mm

MILANO	LAF/FLA (mm)											
Roof inclination angle	10°	14°	18°	22°	25°	30°	35°	40°	45°	50°	55°	60°
GAŚIOR												
LAF	56	54	52	52	50	48	46	46	46	44	44	44
FLA	174	168	162	158	152	148	142	136	132	126	122	118

Cross-section of the roof cover.


Proper assembly depends, inter alia, on the shape of the roof and location of the house, which is why it may be different from the solutions presented here. The best option is to consult a qualified roofer. Please read the guidelines for proper roof ventilation. Details can be found in the information sheets at www.en.roben.pl.



Available colours of roof tiles




MILANO / Black – glaze



MILANO / Copper – engobe



MILANO / Anthracite – engobe



MILANO / Natural red – engobe





Right edge tile



Left edge tile



Ventilating tile



Tile for mounting panels



Double roll tile



Basic ridge tile with a clamp – 2.9 pcs./l.m.



Large, semi-circular initial ridge tile



Ceramic antenna tile



Crest ridge tile end – initial



Crest ridge tile end – final



Venting flue



Ridge tile – crest connector – universal tee model 1



Ridge tile – crest connector – universal tee model 2



Ridge tile – crest connector – cross-piece



Gąsior – łącznik kalenic – trójkąt prosty



Chimney sweep bench 40 cm, set*



Chimney sweep bench 80 cm, set



Ventilation flue with a $\varnothing$ 150 mm connection pipe



Chimney sweep step, set*




Snow catcher*



Anti-snow fence 200 cm, set (copper, brown, chestnut)*



Skylight tile



Roofing tile clamp 4x6



Crest beam clamp



Eaves comb (1 l.m.)



Chimney sweep tape/chimney tape w. 300 mm (1 l.m.)






Ridge tile tape/crest tape w. 300 mm (1 l.m.)



BERGAMO	LAF/FLA (mm)							
Roof inclination angle	25°	30°	35°	40°	45°	50°	55°	60°
RIDGE TILE								
LAF	35	30	28	28	28	30	36	38
FLA	83	75	69	63	55	46	36	31

Flat time



Cross-section of the roof cover.

Proper assembly depends, inter alia, on the shape of the roof and location of the house, which is why it may be different from the solutions presented here.
The best option is to consult a qualified roofer. Please read the guidelines for proper roof ventilation.
Details can be found in the information sheets at www.en.roben.pl.

Technical data*

Weight (1 item)	ca. 3.95 kg
Total length	ca. 43.6 cm
Total width	ca. 28.5 cm
Length of cover	ca. 33.35-35.80 cm
Average width of cover	ca. 23.7 cm
Minimum design value/m ²	ca. 12 items
Quantity/m ²	ca. 11.8-12.8 items
Minimum roof inclination angle	up to 25°
Quantity/EURO pallet	240 items
Weight per sqm	ca. 48.5 kg
Weight of full pallet	ca. 975 kg
Frost resistance	yes

* technical parameters may be slightly changed

Properties

- perfectly flat roof area
- tight cover thanks to precise interlocks
- possibility of putting roof tiles in a series or with a shift

Available colours of roof tiles



Black glaze



Platinum engobe




Anthracite engobe



Nature engobe




perfectly flat roof area



Extreme left roof tile

Extreme right roof tile

BERGAMO / Black – glaze



BERGAMO / Anthracite – engobe





BERGAMO / Platinum – engobe



BERGAMO / Nature – engobe







Technical data*

Weight (1 item)	ca. 3.97 kg
Total length	ca. 47.2 cm
Total width	ca. 29.0 cm
Length of cover	ca. 36.5–40.3 cm
Average width of cover	ca. 24,5 cm
Minimum design value/m ²	ca. 10,1 items
Quantity/m ²	ca. 10.1–11.2 items
Minimum roof inclination angle	up to 22°
Quantity/EURO pallet	240 items
Weight per sqm	ca. 40.1–44.5 kg
Weight of full pallet	ca. 983 kg
Frost resistance	yes


* technical parameters may be slightly changed



Average length of cover ca. 365–403 mm



Properties

- high leaktightness
- strength
- attractive design
- lighter roof
- attractive price
- average length of cover ca. 365–403 mm



PIEMONT	LAF/FLA (mm)									
Roof inclination angle	22°	25°	30°	35°	40°	45°	50°	55°	60°	
RIDGE TILE										
LAF	70	70	65	60	55	55	55	50	50	
FLA	110	105	100	90	85	75	70	60	50	

Flat
time



Cross-section of the roof cover.

Proper assembly depends, inter alia, on the shape of the roof and location of the house, which is why it may be different from the solutions presented here. The best option is to consult a qualified roofer. Please read the guidelines for proper roof ventilation. Details can be found in the information sheets at www.en.roben.pl.

Available colours of roof tiles



Graphite
glaze



Titan grey
glaze



Auburn
noble engobe



Copper
engobe



Brown
engobe




Tobago
glaze



Anthracite
engobe

PIEMONT / Graphite – glaze



PIEMONT / Auburn – noble engobe



PIEMONT / Titan grey – glaze



PIEMONT / Copper – engobe



PIEMONT / Tobago – glaze



PIEMONT / Brown – engobe



PIEMONT / Anthracite – engobe





Left edge tile
(2.5 pcs./l.m.)



Right edge tile
(2.5 pcs./l.m.)



Ventilating tile



1/2 Tile



Tile for mounting
panels



Double roll tile



Terminal edging tile*



Standard edging tile*



Solar tile (1 set = 2 pcs.)



Gąsior - łącznik kalenic
- trójnik kąt prosty



Venting flue with
a 100 mm connection pipe



Ventilation flue with
a 150 mm connection pipe



Chimney sweep bench 40 cm, set*



Chimney sweep bench 80 cm, set



Chimney sweep step, set*



Snow catcher*



Anti-snow fence 200 cm, set
(copper, brown, chestnut)*



Ceramic antenna tile



Basic ridge tile with
a clamp - 2.9 pcs./l.m.



Crest ridge tile end
- initial



Crest ridge tile end
- final



Skylight tile



Roofing tile clamp 4x6



Crest beam clamp



Large, semi-circular
initial ridge tile



Ridge tile - crest connector
- universal tee model 1



Ridge tile - crest connector
- universal tee model 2



Ridge tile - crest connector
- cross-piece



Eaves comb (1 l.m.)



Chimney sweep tape/chimney tape
w. 300 mm (1 l.m.)






Ridge tile tape/crest tape
w. 300 mm (1 l.m.)



MONZA	LAF/FLA (mm)									
Roof inclination angle	22°	25°	30°	35°	40°	45°	50°	55°	60°	
RIDGE TILE										
LAF	65	65	65	50	50	50	40	35	35	
FLA	110	105	100	90	85	80	80	70	65	

Flat
time



Cross-section of the roof cover.

Proper assembly depends, inter alia, on the shape of the roof and location of the house, which is why it may be different from the solutions presented here. The best option is to consult a qualified roofer.
Please read the guidelines for proper roof ventilation. Details can be found in the information sheets at www.en.roben.pl.

Available colours of roof tiles

Technical data*


Weight (1 item).....	ca. 4.07 kg
Total length.....	ca. 46.4 cm
Total width.....	ca. 30.4 cm
Length of cover.....	ca. 38.3–40.3 cm
Average width of cover.....	ca. 26.3 cm
Minimum design value/m ²	ca. 9,5 items
Quantity/m ²	ca. 9.4–9.9 items
Minimum roof inclination angle.....	up to 22°
Quantity/EURO pallet.....	240 items
Weight per sqm.....	ca. 38.3–40.3 kg
Weight of full pallet.....	ca. 1007 kg
Frost resistance.....	yes

* technical parameters may be slightly changed

Properties

- large size
- smaller consumption per m²
– only 9.4–9.9 items are enough!
- fast assembly
- lighter roof
- attractive price

Additional teeth, located at the side edge of the roof tile, guarantee more durable and stable connection of the roof tile to the patch section. ▶



Graphite
glaze



Maduro
glaze



Anthracite
engobe



Tobago
glaze



Copper
engobe



Auburn
noble engobe



Trentino
noble engobe

MONZA / Graphite – glaze



MONZA / Tobago – glaze



MONZA / Anthracite – engobe



MONZA / Maduro – glaze



MONZA / Trentino - noble engobe



MONZA / Auburn - noble engobe



MONZA / Copper - engobe





Left edge tile
(2.5 pcs./l.m.)



Right edge tile
(2.5 pcs./l.m.)



Ventilating tile



1/2 Tile



Tile for mounting
panels



Double roll tile



Standard edging tile*



Right terminal
edging tile



Left terminal
edging tile



Solar tile (1 set = 2 pcs.)



Antenna tile



Crest ridge tile end
- initial



Crest ridge tile end
- final



Basic ridge tile with
a clamp - 2.9 pcs./l.m.



Ridge tile - crest connector
- universal tee model 1



Ridge tile - crest connector
- universal tee model 2



Ridge tile - crest connector
- cross-piece



Large, semi-circular
initial ridge tile



Gąsior - łącznik kalenic
- trójnik ką prosty



Chimney sweep step, set*



Skylight tile



Eaves comb (1 l.m.)



Venting flue with
a Ø 100 mm connection pipe



Ventilation flue with
a Ø 150 mm connection pipe



Chimney sweep bench 40 cm,
set*



Chimney sweep bench 80 cm,
set



Anti-snow fence 200 cm, set
(copper, brown, chestnut)*



Snow catcher*



Roofing tile clamp 4x6



Crest beam clamp



Chimney sweep tape/chimney tape
w. 300 mm (1 l.m.)



Ridge tile tape/crest tape
w. 300 mm (1 l.m.)

Gallery



Factory



Production facilities in Środa Śląska



Röben is a part of a family-owned concern that has been manufacturing ceramic building materials for **more than 160 years**. The Frisian brickyards, established in the mid-19th century, are what today's chain of factories located in Europe and America originated from. In 1995 the factory in Środa Śląska became a part of the company cherishing such a long-established tradition. This is where the largest and the most modern roof tile factory in Europe was established.

There are many factors that contributed to Röben's success. From local deposits of clay we extract a perfect raw material for the production of bricks, clinker tiles, roof tiles and roof accessories. This natural ceramic raw material, combined with the most modern technological solutions and long experience, provides for the highest quality of the building materials manufactured in our factories. They enable further generations of investors to make the dreams of a beautiful and safe home come true. The best technical parameters, strength, an attractive design and a good price constitute a logical whole.

Röben building ceramics. Reach high!

Ceramic roof tiles and accessories **Röben** feature a 30-year long quality warranty.

30 years
of WARRANTY



Röben
GOLD MEDAL
DACH FORUM 2024
IN KIELCE



Röben
Gold Building Brand
of the Year
2020, 2015, 2014,
2010, 2009, 2008,
2006, 2005, 2004
in the category of
Roof Covers



Röben
GOLD MEDAL
MTP POZNAŃ EXPO
2020
Awarded product
Ceramic tile
PIEMONT



Röben
CUSTOMER LAUREL -
TOP BRAND 2018
in the category:
'Quality and innovati-
veness in the building
industry'



Röben
CONSUMER
QUALITY LEADER
2017



PN-EN 1304: January 2007 ceramic roof tiles. Definition and specification of products Annexe B
In case of unicoloured roof tiles the shades of the colour may differ, which stems from specific methods of the production of ceramic products.

The product colours presented in the catalogue are for demonstrative purposes only and their shades may differ from the real colour of the products.
Röben shall bear no liability for any differences between the real colour of the product and the colour presented in the catalogue.



Watch roofing photo gallery:



Factory:

Röben Polska Sp. z o.o. i Wspólnicy Sp. k.
55-300 Środa Śląska, Ceramiczna Street 2
phone no. 71 39 78 100, fax no. 71 39 78 111
e-mail: biuro@roben.pl

www.en.roben.pl